TECH-LINK INTERNATIONAL 76 Upper Maud Street, Ulverstone, TAS 7315, Australia Tel: 61 3 6425 1941, Fax: 61 3 6425 1936

TECH-DRY BUILDING PROTECTION SYSTEMS PTY. LTD. ACN 005 307 684 ABN 62 922 836 289 177-179 Coventry Street, South Melbourne, Victoria 3205, Australia Telephone: 61 3 9699 8202 (all hours) Facsimile: 61 3 9696 3362 Website: www.techdry.com.au E-mail: info@techdry.com.au

Tech-Dry[®]



MATERIAL SAFETY DATA SHEET

TECHDRYAD MORTAR ADDITIVE

Page 1 of 2

Issued: 01/01/2010

Not c	lassified as hazardous accord	ling to criteria of Worksafe A	ustralia
<u>Identification</u>	Product name: Other names: Manufacturer's code: UN number: D.G. class: Subsidiary risk: Hazchem code: Poisons schedule no: Package group:	TECHDRYAD MORTAR ADD Water repellent admixture RPTDADMA Not allocated Not allocated Not allocated Not allocated Not allocated Not allocated Not allocated	DITIVE
<u>Use</u>	Water resistant admixture for	cement and sand mortar for Te	ech-Dry blocks.
Physical properties	Appearance: Boiling point: Vapour pressures (20 °C): Density (20 °C): Flash point: Flammability limits (%): Solubility in water:	Pale yellow clear liquid ≥100 °C Not allocated 1.0 g/ml Not allocated Not allocated Soluble	
Other properties	Autoignition point: Vapour density (air=1): pH: Viscosity (20 °C):	Not allocated Not allocated 8-9 Not allocated	
<u>Ingredients</u>	Chemical entity Fatty acid sodium salt Non-hazardous ingredients Water	CAS number n/a n/a	Proportion <10% <10% To 100%
Hazard Health Informa	tion		
Health Effects:		of this product as a whole ha giene measures should be follo	
<u>Acute:</u> Swallowed:	Harmful if swallowed. It may c	ause discomfort if swallowed.	
Eye:	May cause eye irritation.		
Skin:	May cause skin irritation.		
Inhaled:	Inhalation over intensive vapo coughing and chest discomfor	our may cause irritation of the r t.	nose and throat and cause

Chronic: Not known.

First Aid:	
Swallowed:	If swallowed, do not induce vomiting. Give a glass of water. Never give anything by mouth to an unconscious person. Get prompt medical attention.
Eye:	Flush eyes with copious amounts of water for at least 15 minutes. Obtain medical attention.
Skin:	Remove contaminated clothing and wash skin thoroughly. Wash clothing before reuse. Seek medical advice if effects persist.
Inhaled:	Remove affected victim from exposure area to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek prompt medical advice.
First Aid Facilities:	Washing facilities are strongly recommended for handling chemicals.
Advice to Doctor:	Treat symptomatically.
Precautions For Use	
Exposure Standards:	There is no exposure standard determined for this product. The blanket limit of 10mg/m ³ (TWA and STEL) for dusts or mists may apply. The nature of this product makes it unlikely that this level will be approached in normal use.
Engineering Controls:	Use with sufficient ventilation.
Personal Protection:	Wear chemical resistant safety glasses or goggles, gloves and protective clothing. Wear approved respiratory protection (AS1716/1715) if there is a risk of exposure to intensive vapour concentrations. Wash hands after handling.
Flammability:	Not flammable and not combustible under conditions of use.
Flammability: <u>Safe Handling Informat</u>	
Safe Handling Informat	
Safe Handling Informat	tion Consult AS1940 and relevant state or territory regulations on safe storage and handling. Store in original or approved containers in a cool well-ventilated area away from any heat and ignition sources preferable at 8 °C to 35°C. The product may
Safe Handling Informate Storage and Transport Spills and disposal:	tion Consult AS1940 and relevant state or territory regulations on safe storage and handling. Store in original or approved containers in a cool well-ventilated area away from any heat and ignition sources preferable at 8 °C to 35°C. The product may become solid at below 8 °C but will become normal once temperature is at above 8 °C. Wear full protective clothing while attending to spills. Extinguish all ignition sources. Prevent entry into drainage systems, sewers and waterways. Dam and collect with inert absorbent material such as sand or earth. Ensure waste disposal conforms to
Safe Handling Informate Storage and Transport Spills and disposal:	tion Consult AS1940 and relevant state or territory regulations on safe storage and handling. Store in original or approved containers in a cool well-ventilated area away from any heat and ignition sources preferable at 8 °C to 35°C. The product may become solid at below 8 °C but will become normal once temperature is at above 8 °C. Wear full protective clothing while attending to spills. Extinguish all ignition sources. Prevent entry into drainage systems, sewers and waterways. Dam and collect with inert absorbent material such as sand or earth. Ensure waste disposal conforms to local waste disposal regulations. Shut and remove ignition sources if safe to do so. Use dry powder, sand, and foam and/or carbon dioxide extinguisher. Wear a breathing apparatus and full protective measures while attending to the hazard. Prevent the product from entering drains or waterways. Hazard decomposition products may include carbon oxides and traces of
Safe Handling Information Storage and Transport Spills and disposal: Fire/Explosion Hazard:	tion Consult AS1940 and relevant state or territory regulations on safe storage and handling. Store in original or approved containers in a cool well-ventilated area away from any heat and ignition sources preferable at 8 °C to 35°C. The product may become solid at below 8 °C but will become normal once temperature is at above 8 °C. Wear full protective clothing while attending to spills. Extinguish all ignition sources. Prevent entry into drainage systems, sewers and waterways. Dam and collect with inert absorbent material such as sand or earth. Ensure waste disposal conforms to local waste disposal regulations. Shut and remove ignition sources if safe to do so. Use dry powder, sand, and foam and/or carbon dioxide extinguisher. Wear a breathing apparatus and full protective measures while attending to the hazard. Prevent the product from entering drains or waterways. Hazard decomposition products may include carbon oxides and traces of
Safe Handling Information	tion Consult AS1940 and relevant state or territory regulations on safe storage and handling. Store in original or approved containers in a cool well-ventilated area away from any heat and ignition sources preferable at 8 °C to 35°C. The product may become solid at below 8 °C but will become normal once temperature is at above 8 °C. Wear full protective clothing while attending to spills. Extinguish all ignition sources. Prevent entry into drainage systems, sewers and waterways. Dam and collect with inert absorbent material such as sand or earth. Ensure waste disposal conforms to local waste disposal regulations. Shut and remove ignition sources if safe to do so. Use dry powder, sand, and foam and/or carbon dioxide extinguisher. Wear a breathing apparatus and full protective measures while attending to the hazard. Prevent the product from entering drains or waterways. Hazard decomposition products may include carbon oxides and traces of formaldehyde.

Important Note To the best of our knowledge, the information sources for the preparation of this document were correct and complete at the time of writing. The information is therefore subject to possible change from time to time and cannot be guaranteed. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product or any material existing within the product. For further information, please contact Tech-Dry Building Protection Systems Pty. Ltd.